



Dimensions:

1.3 in. H x 3.1 in. W x 5.7 in. L 33 mm H x 80 mm W x 146 mm L

Weight (including battery):

10.5 oz/ 300 g

Display:

Transflective color TFT-LCD, 65K colors, 240 (W) x 320 (L) (QVGA size)

Touch Panel:

Glass analog resistive touch

Backlight:

LED backlight Main

Battery:

Rechargeable Lithium Ion 1700 mAh (3.7V)

Backup Battery:

Ni-MH battery (rechargeable), 15mAh (2.4V) 2 cells

CPU:

Intel® Xscale™ PXA250

Operating Platform:

Microsoft® Windows® CE 4.1 (CE .NET)

Memory:

32MB RAM/ 32MB ROM

Interface:

RS-232, max. 115.2 kbps min. 1200bps

Communications:

IrDA, 1.2 standard SIR, max. 115.2 kbps, max. standard RS-232 interface CF

Card Slot:

Type II

Cards Supported:

802.11b Spectrum24® card; Bluetooth™ CF card; Type II Flash Memory card

Audio:

Speaker, microphone

Keypad Options:

Standard version and 15-key with power button version 1D

Decode Capability: UPC/EAN/JAN, Code 39, Code 93, Code 128, Interleaved 2 of 5, Discrete 2 of 5, Codabar (NW-7), UCC/EAN-128

LED Display:

Upper front center (amber and green)

Scan Triggers:

Left and right trigger buttons